



Declaration of performance Thin joint Tie 310 AISI 304		
No: GB-DoP-2015-WT-2.1.10		Date: 17-02-16 Version: ENG
1. Unique identification product type	35550 	
2. Indication	Asymmetrical Thin joint Tie 310 Ø4mmx0,5mm AISI 304	
3. Application	Connecting outside-wall with inside-wall with a maximum wall distance 175mm	
4. Applicable	<ul style="list-style-type: none"> -Brick -Silicate elements, and blocks with a compressive strengt >12 N/mm² -Silicateblocks with airholes -Perforated brick -Aereted concrete -Mortar IIa and III, light mortar LM 21 and LM 36 	
5. Name and contact address manufacturer	Gebr. Bodegraven BV Atoomweg 2, 2421 LZ Nieuwkoop 0031 (0)172 520110	
6. Name of authorized representative /	J.A. Bodegraven. Director	
7. System of assessment and verification of the constancy of performance	3	
8. Activity of the Notified Body testing authority in accordance EN 845-1 and EN 846-5	The notified body No. 0764: MPA Bau Hannover: <ul style="list-style-type: none"> • Tests according to EN 846-5 the load values determined. 	
9. European Technical Assessment	EN 845-1	
10. Declared performance according EN 845-1 & EN-846-5		
Essential characteristics	Performance	European Assessment Document
Mechanical strength		
Tensile strength capacity interior wall:	1,80 kN	845-1
Tensile strength capacity outside wall:	1,61 kN	
compressive strength capacity:	0,80 kN	
compressive strengt capacity asymm. 40mm:	0,54 kN	
Minimum embedment length interior waal	90 mm	845-1
Minimum embedment length outside waal	45 mm	
Durability / Material reference RVS 316	4	845-1
<p>11. The performance of the products defined in paragraphs 1 and 2 in accordance with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer referred to in point 4.</p> <p>Nieuwkoop, 17-02-2016</p> <p style="text-align: right;">Getekend,  J.A. Bodegraven, Director</p>		